

KPS 4 Fully Automatic Turntable Wrapper

The KPS 4 is the most powerful, fully automatic standard version solution in our lineup of turntable wrapper systems. With heavy-duty direct friction variable speed drive, it is the best option for high volume users while providing faster high-end performance and quality.



Standard specifications for the powerful KPS 4 automatic turntable wrapper with heavy-duty direct friction variable speed drive are below. However, whatever your needs are, let us know, and we will develop a plan to design and build your customized wrapper.

PERFORMANCE:

- 0-15 RPM
- Turntable size 52" EW, 81" D
- 1 HP AC motor with AC drive, inline reducer
- Direct friction drive
- 20-45 loads/hr. (Dependent on wraps and load)
- Wrap height 80"
- Film capacity 10" roll diameter
- Standard film width 20"
- Maximum load weight 4,000 lbs.
- Allen Bradley Photo-eye load height sensor
- Allen Bradley PLC controls all wrap functions
- Allen Bradley AC drives
- Powder coat finish
- Manual controls for turntable auto/manual
- Manual controls for film carriage raise/lower
- 1/2 HP variable speed AC film carriage lift motor with AC variable speed drive
- Adjustable top and bottom limit switch cams
- Carriage speed adjustment
- Top and bottom wrap selectors
- Film tension adjustment
- Electronic soft start/stop

STRUCTURE:

- Turntable 3/8" steel plate
- Frame: structural steel tube, plate and bar meet ASTM-A36 or ASTM-A500
- Fork lift portability

APPROXIMATE WEIGHT/SIZE:

- 1,600 lbs.
- 200" L x 123" W
- 95 1/2" H

ELECTRICAL:

- 115/1/60Hz 15amp. (Standard outlet)

FILM DELIVERY:

- 20" Variable tension
- 20" Constant pre-stretch
- 20" Powered pre-stretch

kps | **KALAMAZOO**
PACKAGING SYSTEMS

900 47th St SW, Suite J
Wyoming, MI 49509
(616) 534-2600

kalpack.com